

Exinda Network Orchestrator 3062 is the perfect branch office appliance for small and medium businesses. Architected for small branch networks, the 3062 delivers the best price-performance in the category. Network managers who need improved performance for critical network based applications will find the perfect combination of power and speed at a reasonable price point. For branches trying to control inbound internet traffic or prioritize VoIP and video applications, the 3062 is a perfect fit. The 3062 is the most powerful small branch network solution on the market today.

Traffic Shaping

Shaping Throughput	150 Mbps
Concurrent Flows	45,000
New Connections Rate	4,000/s
Packets Per Second	45,000/s
Traffic Policies	512

Traffic Acceleration

Acceleration Throughput	20 Mbps
Edge Cache Throughput	20 Mbps
Accelerated Connections	2,000

Network Diagnostics

APS Objects	100
SLA Objects	100
PDF Objects	20

Interface Capabilities

Built in NICs	Copper: 2 X 1GB bypass bridge pair
Additional NIC Slots	None
Available NICs	None
Management Ports	RJ45 Serial Console, dedicated management GigE NIC
IPMI	None

Physical Characteristics

Form Factor	Desktop unit (optional rackmount kit)
Dimensions (HxWxD)	43mm x 272mm x 268mm (1.7" x 10.6" x 10.38")
Power	External power brick - auto-ranging
Power Rating	14W @ 0.22A (Idle), 15W @ 0.22A (Max)
Weight	2.63 kg (5.8 lbs) including power brick
Data Store / Cache Size	385 GB
Environment	Continuous operation: 5°C to 35°C (41°F to 95°F) , 8%-90% operating humidity